



**PERFORMANCE CHART FOR VERTICAL OPEN WELL SUBMERSIBLE PUMPS SETT**

Open Well Vertical Heavy S.S. Motor S.S. Bowl S.S. Impeller - Radial Flow Type  
Approx Performance Chart at 2880 RPM, 350 to 415 Volts 50Hz Supply

**Three Phase**  
50Hz Supply

**Copper Rotor & Copper Wiring**

RVSS8 SERIES

V-9 MODEL



Item Code	MODEL	MOTOR RATING		STAGE	Outlet IN INCH	TOTAL HEAD IN MITER DISCHARGE IN LITERS PER MINUTE													
		Kw	HP			170	275	330	420	460	485	510	580	660	710	780	960	1040	
NS897	RV-33	3.7	5.0	2	2.5	54	50	46	41	33	29	23							
NS898	RV-34	4.5	6.0	2	2.5		54	50	47	46	44	42	37	30					
NS899	RV-35	5.5	7.5	2	3			52	50	48	46	44	42	37	22				
NS900	RV-36	5.5	7.5	3	2.5	81	75	69	56	50	44	35	30	10					
NS901	RV-37	7.5	10.0	2	4				55	54	53	51	50	47	42	38	33	23	
NS902	RV-38	7.5	10.0	3	3		80	75	70	68	64	62	56	44	32	10			
NS903	RV-39	7.5	10.0	4	3	108	100	90	75	67	59	47							
NS904	RV-40	9.3	12.5	3	4			80	77	73	70	67							
NS905	RV-41	9.3	12.5	4	3			99	95	90	82	73	68	55	43	22			
NS906	RV-42	9.3	12.5	5	3	134	124	115	94	84	74	68	58	25					
NS907	RV-43	11.0	15.0	3	4				80	78	76	75	73	69	62	58	50	32	
NS908	RV-44	11.0	15.0	4	3			110	102	98	92	90	83	75	59	47	20		
NS909	RV-45	11.0	15.0	5	3			115	110	108	105	102	94	74	65	32			
NS910	RV-46	15.0	20.0	4	4				107	102	100	99	85	82	80	77	43	38	
NS911	RV-47	15.0	20.0	5	4				134	120	118	115	110	105	94	74	68	40	
NS912	RV-48	15.0	20.0	6	4		160	150	138	133	130	126	113	89	70	41	30		

