



Suitable for V-4 (100mm) bore well

Approx performance chart at 2800 RPM, 160 to 230 Volts
V-4 Deluxe Motor Full S.S. & PUMP C.I. Bowl S.S. Impeller- MIXED Flow Type

Single Phase
50Hz Supply

Copper Rotor & Copper Wiring

RCQ4 SERIES

Qlpm : Water Outlet 2.5" / 65mm

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER							in mm
		Kw	HP		0.0	85	180	240	310	430	510	
NS 322	RCQS-13	0.75	1.0	3	15	12	11	9	6	4.5	1.5	1.5
NS 323	RCQS-14	0.75	1.0	4	20	16	15	12	7	6	1.5	1.5
NS 324	RCQS-154	1.1	1.5	4	21	17	16	13	8	6	1.5	1.5
NS 325	RCQS-155	1.1	1.5	5	26	21	19	15	10	7.5	1.5	2.5
NS 326	RCQS-26	1.5	2.0	6	31	25	22	18	12	9	1.5	2.5
NS 327	RCQS-27	1.5	2.0	7	36	29	26	21	14	10	1.5	2.5
NS 328	RCQS-38	2.2	3.0	8	41	33	30	24	16	12	1.5	4.0
NS 329	RCQS-310	2.2	3.0	10	51	42	38	30	20	15	1.5	4.0



Suitable for V-4 (100mm) bore well

Approx performance chart at 2800 RPM, 350 to 415 Volts
V-4 Deluxe Motor Full S.S. & PUMP C.I. Bowl S.S. Impeller- MIXED Flow Type

Three Phase
50Hz Supply

RCQ4 SERIES

Qlpm : Water Outlet 2.5" / 65mm

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER							in mm
		Kw	HP		0.0	85	180	240	310	430	510	
NS 330	RCQ-13	0.75	1.0	3	15	12	11	9	6	4.5	1.5	1.5
NS 331	RCQ-14	0.75	1.0	4	20	16	15	12	8	6	1.5	1.5
NS 332	RCQ-154	1.1	1.5	4	21	17	16	13	8	6	1.5	1.5
NS 333	RCQ-155	1.1	1.5	5	26	21	19	15	10	7.5	1.5	1.5
NS 334	RCQ-26	1.5	2.0	6	31	25	22	18	12	9	1.5	2.5
NS 335	RCQ-27	1.5	2.0	7	36	29	26	21	14	10	1.5	2.5
NS 336	RCQ-38	2.2	3.0	8	41	33	30	24	16	12	1.5	4.0
NS 337	RCQ-310	2.2	3.0	10	50	41	38	30	20	15	1.5	4.0
NS 338	RCQ-48	3.0	4.0	8	42	34	31	25	17	12	1.5	4.0
NS 339	RCQ-410	3.0	4.0	10	51	42	38	30	21	15	1.5	4.0
NS 340	RCQ-510	3.7	5.0	10	52	43	38	32	22	16	1.5	4.0
NS 341	RCQ-512	3.7	5.0	12	62	50	45	36	24	18	1.5	4.0
NS 342	RCQ-614	4.5	6	14	72	58	52	42	28	21	1.5	4.0
NS 343	RCQ-7516	5.5	7.5	16	83	65	59	45	32	24	1.5	4.0

