



Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
V-6 Super Motor Full S.S. And S.S. Bowl With S.S. Impeller - RADIAL Flow Type

**Three Phase
50Hz Supply**

Copper Rotor & Copper Wiring

RSK6 SERIES

Qlpm : Water Outlet 2" / 50mm

50 FEET HEAD PER STAGE

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER								in mm
		Kw	HP		30	50	70	80	95	125	140		
NS516	RSK-437	2.2	3.0	7	100	98	90	84	70	49	35	2.5	
NS517	RKS-4410	3.0	4.0	10	145	140	130	120	100	70	50	2.5	
NS518	RSK-4512	3.7	5.0	12	174	168	155	144	120	84	60	4.0	
NS519	RSK-4614	4.5	6.0	14	202	195	180	168	140	98	70	4.0	
NS520	RSK-47518	5.5	7.5	18	260	250	232	216	180	125	90	6	
NS521	RSK-41024	7.5	10.0	24	346	335	310	288	240	167	120	4X4	
NS522	RSK-41230	9.3	12.5	30	430	415	395	360	300	210	150	4X4	
NS523	RSK-41536	11.0	15	36	520	500	465	430	355	250	180	4X4	



RSK6 SERIES

Qlpm : Water Outlet 2" / 50mm

50 FEET HEAD PER STAGE

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER								in mm
		Kw	HP		30	50	80	120	140	170	195		
NS524	RSK-536	2.2	3.0	6	93	84	78	66	54	42	18	2.5	
NS525	RSK-548	3.0	4.0	8	124	112	104	88	72	56	24	2.5	
NS526	RSK-5510	3.7	5.0	10	156	140	130	110	90	70	30	2.5	
NS527	RSK-5612	4.5	6.0	12	187	168	156	132	108	84	36	4.0	
NS528	RSK-57515	5.5	7.5	15	234	210	195	165	135	105	45	4.0	
NS529	RSK-51020	7.5	10.0	20	310	280	260	220	180	140	60	4X4	
NS530	RSK-51225	9.3	12.5	25	390	350	325	275	225	175	75	4X4	
NS531	RSK-51530	11.0	15	30	470	420	390	330	270	210	90	4X4	



RSK6 SERIES

Qlpm : Water Outlet 2" / 50mm

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER								in mm
		Kw	HP		40	60	90	150	165	180	230		
NS532	RSK-635	202	3.0	5	78	70	65	55	45	35	15	2.5	
NS533	RSK-647	3.0	4.0	7	109	98	91	77	63	49	21	2.5	
NS534	RSK-658	3.7	5.0	8	125	112	104	88	72	56	24	2.5	
NS535	RSK-6610	4.5	6.0	10	157	140	130	110	90	70	30	2.5	
NS536	RSK-67512	5.5	7.5	12	188	168	156	132	108	84	36	4.0	
NS537	RSK-61016	7.5	10.0	16	250	224	208	176	144	112	48	2.5X2.5	
NS538	RSK-61220	9.3	12.5	20	314	280	260	220	180	140	60	2.5X2.5	
NS539	RSK-61524	11.0	15.0	24	376	336	312	264	216	168	72	4X4	
NS540	RSK-61726	13.0	17.5	26	408	364	338	286	234	182	78	4X4	
NS541	RSK-62030	15.0	20.0	30	471	420	390	330	270	210	90	4X4	



V-6
Super Model

Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
V-6 Super Motor S.S. And S.S. Bowl With S.S. Impeller - RADIAL Flow Type

Three Phase
50Hz Supply

Copper Rotor & Copper Wiring

RSK6 SERIES Qlpm : Water Outlet 2" / 50mm **50 FEET HEAD PER STAGE**

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					50	100	145	180	220	270	310		
					Loading per Stage : 0.800 Duty point Head per Stage : 12.0mt								
NS542	RSK-834	2.2	3.0	4	62	56	52	48	40	28	12	2.5	
NS543	RSK-845	3.0	4.0	5	78	70	65	60	50	35	15	2.5	
NS544	RSK-856	3.7	5.0	6	93	84	78	72	60	42	18	2.5	
NS545	RSK-868	4.5	6.0	8	124	112	104	96	80	56	24	2.5	
NS546	RSK-87510	5.5	7.5	10	156	140	130	120	100	70	30	4.0	
NS547	RSK-81012	7.5	10.0	12	187	168	156	144	120	84	36	2.5X2.5	
NS548	RSK-81215	9.3	12.5	15	234	210	195	180	150	105	45	2.5X2.5	
NS549	RSK-81518	11.0	15.0	18	280	252	234	216	180	126	54	4X4	
NS550	RSK-81721	13.0	17.5	21	327	294	273	252	210	147	63	4X4	
NS551	RSK-82024	15.0	20.0	24	374	336	312	288	240	168	72	4X4	
NS552	RSK-82530	18.5	25	30	470	420	390	330	270	210	90	4X4	

RSK6 SERIES Qlpm : Water Outlet 2" / 50mm **50 FEET HEAD PER STAGE**

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					80	170	210	250	295	355	410		
					Loading per Stage : 1.000 Duty point Head per Stage : 12.0mt								
NS553	RSK-133	2.2	3.0	3	46	42	39	36	30	21	9	2.5	
NS554	RSK-144	3.0	4.0	4	62	56	52	48	40	28	12	2.5	
NS555	RSK-155	3.7	5.0	5	78	70	65	60	50	35	15	2.5	
NS556	RSK-166	4.5	6.0	6	93	98	78	72	60	42	18	2.5	
NS557	RSK-1758	5.5	7.5	8	124	112	104	96	80	56	24	4.0	
NS558	RSK-11010	7.5	10.0	10	156	140	130	120	100	70	30	2.5X2.5	
NS559	RSK-11212	9.3	12.5	12	187	168	156	144	120	84	36	2.5X2.5	
NS560	RSK-11515	11.0	15.0	15	234	213	195	180	150	105	45	4X4	
NS561	RSK-12020	15.0	20.0	20	312	280	260	240	200	140	60	4X4	
NS562	RSK-12525	18.5	25	25	390	350	325	275	225	175	75	4X4	

RSK6 SERIES Qlpm : Water Outlet 2.5" / 60mm **50 FEET HEAD PER STAGE**

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					100	230	270	310	410	480	510		
					Loading per Stage : 1.250 Duty point Head per Stage : 12.0mt								
NS563	RSK-1243	3.0	4.0	3	46	42	39	36	27	18	9	2.5	
NS564	RSK-1254	3.4	5.0	4	61	56	52	48	36	24	12	2.5	
NS565	RSK-1265	4.5	6.0	5	77	70	65	60	45	30	15	2.5	
NS566	RSK-12756	5.5	7.5	6	92	84	78	72	54	36	18	4.0	
NS567	RSK-12108	7.5	10.0	8	123	112	104	96	72	48	24	2.5X2.5	
NS568	RSK-121210	9.3	12.5	10	154	140	130	120	90	60	30	2.5X2.5	
NS569	RSK-121512	11.0	15.0	12	184	168	156	144	108	72	36	4X4	
NS570	RSK-121714	13.0	17.5	14	215	196	182	168	126	84	42	4X4	
NS571	RSK-122016	15.0	20.0	16	246	224	208	192	144	96	48	4X4	
NS572	RSK-122520	18.5	25	20	312	280	260	240	200	140	60	4X4	





Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
V-6 Super Motor S.S. And C.I. Bowl With S.S. Impeller - RADIAL Flow Type

Three Phase
50Hz Supply

Copper Rotor & Copper Wiring

RSK6 SERIES

Qlpm : Water Outlet 3" / 80mm

50 FEET HEAD PER STAGE



RCQ-150		DISCHARGE HEAD IN METER			Loading per Stage : 1.500 Duty point Head per Stage : 12.0mt							
Item Code	MODEL	MOTOR RATING	STAGE	in mm								
		Kw		HP	110	120	130	140	150	160	170	180
NS573	RSK-1532	2.2	3.0	2	30	28	26	24	18	12	6	2.5
NS574	RSK-1553	3.7	5.0	3	45	42	39	36	27	18	9	2.5
NS575	RSK-1564	4.5	6.0	4	60	56	53	48	36	24	12	2.5
NS576	RSK-15755	5.5	7.5	5	76	70	65	60	45	30	15	4.0
NS577	RSK-15107	7.5	10.0	7	106	98	91	84	63	42	21	2.5X2.5
NS578	RSK-15128	9.3	12.5	8	121	112	104	96	72	48	24	2.5X2.5
NS579	RSK-151510	11.0	15.0	10	152	140	130	120	90	60	30	4X4
NS580	RSK-121712	13.0	17.5	12	182	168	156	144	108	72	36	4X4
NS581	RSK-152013	20.0	20.0	13	197	182	169	156	117	78	39	4X4
NS582	RSK-152516	18.5	25	16	246	224	208	192	149	96	48	4X4

RSK6 SERIES

Qlpm : Water Outlet 2.5" / 65mm

50 FEET HEAD PER STAGE

RSK-200		DISCHARGE HEAD IN METER			Loading per Stage : 2.000 Duty point Head per Stage : 11.5mt							
Item Code	MODEL	MOTOR RATING	STAGE	in mm								
		Kw		HP	122	130	140	150	160	170	180	
NS583	RSK-2042	3.0	4.0	2	30	28	24	23	18	12	6	2.5
NS584	RSK-2063	4.5	6.0	3	45	42	36	35	27	18	9	2.5
NS585	RSK-20754	5.5	7.5	4	60	56	48	46	36	24	12	4.0
NS586	RSK-20105	7.5	10.0	5	75	70	60	58	45	30	15	2.5X2.5
NS587	RSK-20126	9.3	12.5	6	90	84	72	69	54	36	18	2.5X2.5
NS588	RSK-20158	11.0	15.0	8	120	112	96	92	72	48	24	4X4
NS589	RSK-20179	13.0	17.5	9	135	126	108	104	81	54	27	4X4
NS590	RSK-202010	15.0	20.0	10	150	140	120	115	90	60	30	4X4
NS591	RSK-202512	18.5	25	12	182	168	156	144	108	72	36	4X4