



Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
V-6 Deluxe Motor Full S.S. And C.I. Bowl With Nylon Diffuser Nylon Impeller Pump - RIDIAL Flow Type

Three Phase
50Hz Supply

Copper Rotor & Copper Wiring

RSKC6 SERIES

Qlpm : Water Outlet 2" / 50mm

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					0.0	40	70	100	120	155	185		
NS592	RSKC-536	2.2	3.0	6	87	78	72	66	54	42	18	2.5	
NS593	RSKC-548	3.0	4.0	8	116	104	96	88	72	56	24	2.5	
NS594	RSKC-5510	3.7	5.0	10	145	130	120	110	90	70	30	2.5	
NS595	RSKC-5612	4.5	6.0	12	174	156	144	132	108	84	36	4.0	
NS596	RSKC-57515	5.5	7.5	15	217	195	180	165	135	105	45	4.0	

RSKC6 SERIES

Qlpm : Water Outlet 2" / 50mm

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					0.0	50	75	120	140	165	220		
NS597	RSKC-635	2.2	3.0	5	73	70	65	55	45	35	15	2.5	
NS598	RSKC-647	3.0	4.0	7	102	98	91	77	63	49	21	2.5	
NS599	RSKC-658	3.7	5.0	8	117	112	104	88	72	56	24	2.5	
NS600	RSKC-6610	4.5	6.0	10	147	140	130	110	90	70	30	2.5	
NS601	RSKC-67512	5.5	7.5	12	176	168	156	132	108	84	36	4.0	
NS602	RSKC-61016	7.5	10.0	16	234	224	208	176	144	112	48	2.5X2.5	
NS603	RSKC-61220	9.3	12.5	20	294	280	260	220	180	140	60	2.5X2.5	
NS604	RSKC-61524	11.0	15.0	24	352	336	312	264	216	168	72	4X4	
NS605	RSKC-61726	13.0	17.5	26	382	364	338	284	234	182	78	4X4	

RSKC6 SERIES

Qlpm : Water Outlet 2" / 50mm

Item Code	MODEL	MOTOR Kw	RATING HP	STAGE	DISCHARGE HEAD IN METER								in mm
					0.0	80	140	180	220	270	310		
NS606	RSKC-834	2.2	3.0	4	59	56	52	48	40	28	15	2.5	
NS607	RSKC-845	3.0	4.0	5	73	70	65	60	50	35	15	2.5	
NS608	RSKC-856	3.7	5.0	6	87	84	78	72	60	42	18	2.5	
NS609	RSKC-868	4.5	6.0	8	116	112	104	96	80	56	24	2.5	
NS610	RSKC-84510	5.5	7.5	10	146	140	130	120	100	70	30	4.0	
NS611	RSKC-81012	7.5	10.0	12	175	168	156	144	120	84	36	2.5X2.5	
NS612	RSKC-81215	9.3	12.5	15	220	210	195	180	150	105	45	2.5X2.5	
NS613	RSKC-81518	11.0	15.0	18	262	252	234	216	180	126	54	4X4	
NS614	RSKC-81721	13.0	17.5	21	306	294	273	252	210	147	63	4X4	





Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
 V-6 Deluxe Motor Full S.S. And C.I. Bowl With Nylon Diffuser Nylon Impeller Pump - RADIAL Flow Type

Three Phase
 50Hz Supply

Copper Rotor & Copper Wiring

RSKC6 SERIES

Qlpm : Water Outlet 2" / 50mm

RSKC-100		DISCHARGE HEAD IN METER				Loading per Stage : 2.000 Duty point Head per Stage : 7.0mt						in mm
Item Code	MODEL	MOTOR	RATING	STAGE	0.0	110	180	230	290	355	410	
		Kw	HP									
NS615	RSKC-133	2.2	3.0	3	43	42	39	36	30	21	9	2.5
NS616	RSKC-144	3.0	4.0	4	56	56	52	48	40	28	12	2.5
NS617	RSKC-155	3.7	5.0	5	73	70	65	60	50	35	15	2.5
NS618	RSKC-166	4.5	6.0	6	87	98	78	72	60	42	18	2.5
NS619	RSKC-1758	5.5	7.5	8	116	112	104	96	80	56	24	4.0
NS620	RSKC-11010	7.5	10.0	10	146	140	130	120	100	70	30	2.5X2.5
NS621	RSKC-11212	9.3	12.5	12	175	168	156	144	120	84	36	2.5X2.5
NS622	RSKC-11515	11.0	15.0	15	220	213	195	180	150	105	45	4X4
NS623	RSKC-12020	15.0	20.0	20	292	280	260	240	200	140	60	4X4

RSKC6 SERIES

Qlpm : Water Outlet 2.5" / 65mm

RSKC-125		DISCHARGE HEAD IN METER				Loading per Stage : 1.250 Duty point Head per Stage : 11.0mt						in mm
Item Code	MODEL	MOTOR	RATING	STAGE	0.0	170	220	275	380	440	475	
		Kw	HP									
NS624	RSKC-1243	3.0	4.0	3	43	42	39	33	27	18	9	2.5
NS625	RSKC-1254	3.7	5.0	4	57	56	53	44	36	24	12	2.5
NS626	RSKC-1265	4.5	6.0	5	72	70	65	55	45	30	15	2.5
NS627	RSKC-12756	5.5	7.5	6	86	84	78	66	54	36	18	4.0
NS628	RSKC-12108	7.5	10.0	8	115	112	104	88	72	48	24	2.5X2.5
NS629	RSKC-121210	9.3	12.5	10	144	140	130	110	90	60	30	2.5X2.5
NS630	RSKC-121512	11.0	15.0	12	172	168	156	132	108	72	36	4X4
NS631	RSKC-121714	13.0	17.5	14	200	196	182	154	126	84	42	4X4
NS632	RSKC-122016	15.0	20.0	16	250	224	208	176	144	96	48	4X4

RSKC6 SERIES

Qlpm : Water Outlet 2.5" / 65mm

RSKC-150		DISCHARGE HEAD IN METER				Loading per Stage : 1.500 Duty point Head per Stage : 11.0mt						in mm
Item Code	MODEL	MOTOR	RATING	STAGE	0.0	185	270	320	450	570	590	
		Kw	HP									
NS633	RSKC-1532	2.2	3.0	2	28	28	26	22	18	12	6	2.5
NS634	RSKC-1553	3.7	5.0	3	42	42	39	33	27	18	9	2.5
NS635	RSKC-1564	4.5	6.0	4	57	56	52	44	36	24	18	2.5
NS636	RSKC-15755	5.5	7.5	5	71	70	65	55	45	30	15	4.0
NS637	RSKC-15107	7.5	10.0	7	99	98	91	77	63	42	21	2.5X2.5
NS638	RSKC-15128	9.3	12.5	8	113	112	104	88	72	48	24	2.5X2.5
NS639	RSKC-151510	11.0	15.0	10	142	140	130	110	90	60	30	4X4
NS640	RSKC-151712	13.0	17.5	12	170	168	156	132	108	72	36	4X4
NS641	RSKC-152013	15.0	20.0	13	184	182	169	143	117	78	39	4X4





Suitable for V-6 (150mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 Volts
 V-6 Deluxe Motor Full S.S. And C.I. Bowl With Nylon Diffuser Nylon
 Impeller Pump - RIDIAL Flow Type

**Three Phase
 50Hz Supply**

Copper Rotor & Copper Wiring

RSKC6 SERIES

Qlpm : Water Outlet 2" / 65mm

50FEET HEAD PER STAGE

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER								in mm
		Kw	HP		0.0	280	400	450	585	680	760		
NS642	RSKC-2042	3.0	4.0	2	28	26	24	21	18	12	6	2.5	
NS643	RSKC-2063	4.5	6.0	3	42	39	36	32	27	18	9	2.5	
NS644	RSKC-20764	5.5	7.5	4	56	52	48	42	36	24	12	4.0	
NS645	RSKC-20105	7.5	10.0	5	70	65	60	53	45	30	15	2.5X2.5	
NS646	RSKC-20126	9.3	12.5	6	84	78	72	63	54	36	18	2.5X2.5	
NS647	RSKC-20158	11.0	15.0	8	112	104	96	84	72	48	24	4X4	
NS648	RSKC-20179	13.0	17.5	9	126	117	108	95	81	54	27	4X4	
NS649	RSKC-202010	15.0	20.0	10	140	120	120	105	90	60	30	4X4	

WIDE RANGE OF V6 PUMPS

