



Suitable for V-8 (200mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 volts
 V-8 Super motor S.S. and C.I. Bowl With S.S. Impeller Radial Flow
Copper Rotor & Copper Wiring

Three Phase
 50Hz Supply



JCK8 SERIES Qlpm : Water Outlet 3" / 75mm **SUITABLE FOR 200MM BORWELL**

JCK-250		DISCHARGE HEAD IN METER			Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
Item Code	MODEL	MOTOR	RATING	STAGE							
		Kw	HP		280	340	400	450	520	580	640
NS 650	JCK-825104	7.5	10	4	73	69	65	60	54	47	39
NS 651	JCK-825125	9.4	12.5	5	91	87	81	75	68	59	49
NS 652	JCK-825156	11.3	15	6	110	104	98	90	81	71	59
NS 653	JCK-825177	13.1	17.5	7	128	122	114	105	95	82	68
NS 654	JCK-825208	15.0	20	8	146	139	130	120	108	94	78
NS 655	JCK-8252510	18.8	25	10	183	174	163	150	135	118	98
NS 656	JCK-8253012	22.5	30	12	219	208	195	180	162	141	117
NS 657	JCK-8253514	26.3	35	14	256	243	228	210	189	165	137

JCK8 SERIES Qlpm : Water Outlet 3" / 75mm **SUITABLE FOR 200MM BORWELL**

JCK-300		DISCHARGE HEAD IN METER			Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
Item Code	MODEL	MOTOR	RATING	STAGE							
		Kw	HP		360	420	480	550	600	680	720
NS 658	JCK-830103	7.5	10	3	55	52	49	45	41	35	29
NS 659	JCK-830124	9.4	12.5	4	73	70	65	60	54	47	39
NS 660	JCK-830155	11.3	15	5	91	87	81	75	68	59	49
NS 661	JCK-830176	13.1	17.5	6	110	104	98	90	81	71	59
NS 662	JCK-830207	15	20	7	128	122	114	105	95	82	68
NS 663	JCK-830258	18.8	25	8	146	139	130	120	108	94	78
NS 664	JCK-8303010	22.5	30	10	183	174	163	150	135	118	98
NS 665	JCK-8303511	26.3	35	11	201	191	179	165	149	129	107
NS 666	JCK-8303512	26.3	35	12	219	209	195	180	162	141	117
NS 667	JCK-8304014	30	40	14	256	243	228	210	189	165	137
NS 668	JCK-8304415	33.8	45	15	274	261	244	225	203	176	146
NS 669	JCK-8305016	37.5	50	16	292	278	260	240	216	188	156

JCK8 SERIES Qlpm : Water Outlet 3" / 75mm **SUITABLE FOR 200MM BORWELL**

JCK-400		DISCHARGE HEAD IN METER			Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
Item Code	MODEL	MOTOR	RATING	STAGE							
		Kw	HP		450	550	650	750	800	900	950
NS 670	JCK-840123	9.4	12.5	3	55	53	50	45	41	35	29
NS 671	JCK-840154	11.3	15	4	74	70	66	60	54	46	39
NS 672	JCK-840205	15	20	5	93	88	83	75	68	58	49
NS 673	JCK-840256	18.8	25	6	111	105	99	90	81	69	59
NS 674	JCK-840257	18.5	25	7	130	123	116	105	95	81	68
NS 675	JCK-840307	22.5	30	7	130	123	116	105	95	81	68
NS 676	JCK-840308	22.5	30	8	148	140	132	120	108	92	78
NS 677	JCK-840359	26.3	35	9	167	158	149	135	122	104	88
NS 678	JCK-8404010	30	40	10	185	175	165	150	135	115	98
NS 679	JCK-8404511	33.8	45	11	204	193	182	165	149	127	107
NS 680	JCK-8404512	33.8	45	12	222	210	198	180	162	138	117
NS 681	JCK-8405012	37.5	50	12	222	210	198	180	162	138	117
NS 682	JCK-8405014	37.5	50	14	259	245	231	210	189	161	137



Suitable for V-8 (200mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 volts
V-8 Super motor S.S. and C.I. Bowl With S.S. Impeller Radial Flow

Three Phase
50Hz Supply

Copper Rotor & Copper Wiring

JCK8 SERIES Qlpm : Water Outlet 3" / 75mm SUITABLE FOR 200MM BORWELL

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER						
		Kw	HP		Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
					750	825	900	975	1050	1125	1200
JCK-850102		7.5	10	2	37	36	33	30	26	23	20
JCK-850153		11.3	15	3	56	53	50	45	39	34	29
JCK-850204		15	20	4	74	71	66	60	52	45	39
JCK-850255		18.8	25	5	93	89	83	75	65	56	49
JCK-850306		22.5	30	6	111	107	99	90	78	68	59
JCK-850357		26	35	7	130	124	116	105	91	79	68
JCK-850408		30	40	8	148	142	132	120	104	90	78
JCK-850459		33.8	45	9	167	160	149	135	117	101	88
JCK-8505010		37.5	50	10	185	178	165	150	130	113	98
JCK-8505011		37.5	50	11	204	193	182	165	149	127	107
JCK-8506012		45	60	12	222	213	198	180	156	135	107

JCK8 SERIES Qlpm : Water Outlet 3" / 75mm SUITABLE FOR 200MM BORWELL

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER						
		Kw	HP		Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
					825	950	1050	1150	1275	1350	1425
JCK-860122		9.4	12.5	2	38	36	34	30	27	24	20
JCK-860173		13.1	17.5	3	56	53	50	45	41	35	29
JCK-860254		18.8	25	4	75	71	67	60	54	47	39
JCK-860305		22.5	30	5	94	89	84	75	68	59	49
JCK-860356		26.3	35	6	113	107	101	90	81	71	59
JCK-860407		30	40	7	131	124	117	105	95	82	68
JCK-860508		37.5	50	8	150	142	134	120	108	94	78
JCK-8606010		45	60	10	188	178	168	150	135	118	98

JCK8 SERIES Qlpm : Water Outlet 3" / 75mm SUITABLE FOR 200MM BORWELL

Item Code	MODEL	MOTOR RATING		STAGE	DISCHARGE HEAD IN METER						
		Kw	HP		Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
					950	1025	1150	1250	1375	1450	1525
JCK-870152		11.3	15	2	38	36	34	30	27	24	20
JCK-870203		15	20	3	56	53	51	45	41	41	29
JCK-870355		26.3	35	5	94	89	85	75	68	68	49
JCK-870406		30	40	6	113	107	102	90	81	81	59
JCK-870507		37.5	50	7	131	124	119	105	95	95	68
JCK-870609		45	60	9	169	160	153	135	122	122	88
JCK-8707510		56.3	75	10	188	178	170	150	135	135	98

