



Suitable for V-8 (200mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 volts
V-8 Super motor S.S. and C.I. Bowl With S.S. Impeller - Mix Flow

Three Phase
50Hz Supply

JCQ8 SERIES Qlpm : Water Outlet 3" / 75mm SUITABLE FOR 200MM BORWELL

JCQ-300		DISCHARGE HEAD IN METER			Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
Item Code	MODEL	MOTOR	RATING	STAGE	400	525	600	750	825	925	1000
		Kw	HP								
NS709	JCQ-830103	7.5	10	3	47	45	42	39	38	35	33
NS710	JCQ-830124	9.4	12.5	4	63	60	56	52	50	47	44
NS711	JCQ-830155	11.3	15	5	79	75	70	65	63	59	55
NS712	JCQ-830206	15	20	6	95	90	84	78	75	71	66
NS713	JCQ-830207	15	20	7	110	105	98	91	88	82	77
NS714	JCQ-830258	18.5	25	8	126	120	112	104	100	94	88
NS715	JCQ-8303010	22.5	30	10	158	150	140	130	125	118	110
NS716	JCQ-8303511	26.3	35	11	173	165	154	143	138	129	121
NS717	JCQ-8303512	26.3	35	12	189	180	168	156	150	141	132
NS718	JCQ-8304012	30	40	12	189	180	168	156	150	141	132
NS719	JCQ-8304014	30	40	14	221	210	196	182	175	165	154
NS720	JCQ-8304514	33.8	45	14	221	210	196	182	175	165	154
NS721	JCQ-8304515	33.8	45	15	236	225	210	195	188	176	165



JCQ8 SERIES Qlpm : Water Outlet 4" / 100mm SUITABLE FOR 200MM BORWELL

JCQ-400		DISCHARGE HEAD IN METER			Loading per Stage : 0.400 Duty point Head per Stage : 7mt						
Item Code	MODEL	MOTOR	RATING	STAGE	625	700	800	925	1025	1150	1275
		Kw	HP								
NS722	JCQ-84072	5.6	7.5	2	34	32	30	28	26	23	20
NS723	JCQ-840123	9.4	12.5	3	50	48	45	42	38	35	30
NS724	JCQ-840154	11.3	15	4	67	64	60	56	51	46	40
NS725	JCQ-840205	15	20	5	84	80	75	70	64	58	50
NS726	JCQ-840256	18.8	25	6	101	96	90	84	77	69	60
NS727	JCQ-840257	18.8	25	7	117	112	105	98	89	81	70
NS728	JCQ-840307	22.5	30	7	117	112	105	98	89	81	70
NS729	JCQ-840308	22.5	30	8	134	128	120	112	102	92	80
NS730	JCQ-840359	26.3	35	9	151	144	135	126	115	104	90
NS731	JCQ-8403510	26.3	35	10	168	160	150	140	128	115	100
NS732	JCQ-8404010	30	40	10	168	160	150	140	128	115	100
NS733	JCQ-8404011	30	40	11	184	176	165	154	140	127	110
NS734	JCQ-8404511	33.8	45	11	184	176	165	154	140	127	110
NS735	JCQ-8404512	33.8	45	12	201	192	180	168	153	138	120
NS736	JCQ-8405012	37.5	50	12	201	192	180	168	153	138	120
NS737	JCQ-8405013	37.5	50	13	235	224	210	196	179	161	140
NS738	JCQ-8406014	45	60	14	235	224	210	196	179	161	140
NS739	JCQ-84	45	60	15	251	240	225	21	191	173	150



Suitable for V-8 (200mm) bore well

Approx performance chart at 2880 RPM, 350 to 415 volts
V-8 Super motor full S.S. and C.I. Bowl With S.S. Impeller - Mix Flow

Three Phase
50Hz Supply

Copper Rotor & Copper Wiring



JCQ8 SERIES Qlpm : Water Outlet 4" / 100mm SUITABLE FOR 200MM BORWELL

JCQ-500		DISCHARGE HEAD IN METER				Loading per Stage : 0.400 Duty point Head per Stage : 7mt					
Item Code	MODEL	MOTOR RATING		STAGE	700	850	1000	1150	1225	1350	1475
		Kw	HP								
NS740	JCQ-850102	7.5	10	2	34	32	30	28	26	23	21
NS741	JCQ-850153	11.3	15	3	50	48	45	42	38	35	31
NS742	JCQ-850204	15	20	4	67	64	60	56	51	46	41
NS743	JCQ-850255	18.8	25	5	84	80	75	70	64	58	51
NS744	JCQ-850306	22.5	30	6	101	96	90	84	77	69	62
NS745	JCQ-850357	26.3	35	7	117	112	105	98	89	81	72
NS746	JCQ-850408	30	40	8	134	128	120	112	102	92	82
NS747	JCQ-850459	33.8	45	9	151	144	135	126	115	104	92
NS748	JCQ-8505010	37.5	50	10	168	160	150	140	128	115	103
NS749	JCQ-8505011	37.5	50	11	184	176	165	154	140	127	110
NS750	JCQ-8506012	45	60	12	201	192	180	168	153	138	123
NS751	JCQ-8507515	56.3	75	15	251	240	225	210	191	173	154

JCQ8 SERIES Qlpm : Water Outlet 4" / 100mm SUITABLE FOR 200MM BORWELL

JCQ-600		DISCHARGE HEAD IN METER				Loading per Stage : 0.400 Duty point Head per Stage : 7mt					
Item Code	MODEL	MOTOR RATING		STAGE	925	1050	1225	1350	1430	1525	1600
		Kw	HP								
NS752	JCQ-860122	9.4	12.5	2	35	33	30	28	26	23	21
NS753	JCQ-860173	13.1	17.5	3	53	50	45	42	39	35	31
NS754	JCQ-860254	18.8	25	4	70	66	60	56	52	46	41
NS755	JCQ-860305	22.5	30	5	88	83	75	70	65	58	51
NS756	JCQ-860356	26.3	35	6	105	99	90	84	78	69	62
NS757	JCQ-860407	30	40	7	123	116	105	98	91	81	72
NS758	JCQ-860458	33.8	45	8	140	132	120	112	104	92	82
NS759	JCQ-860508	37.5	50	8	140	132	120	112	104	92	82
NS760	JCQ-860509	37.5	50	9	158	149	135	126	117	104	92
NS761	JCQ-8606010	45	60	10	175	165	150	140	130	115	103
NS762	JCQ-8607512	56.3	75	12	210	198	180	168	156	138	123
NS763	JCQ-8608514	63.8	85	14	245	231	210	196	182	161	144